

Splitters

Product Description

These multi purpose splitters are designed to divide an incoming RF signal equally into 2, 3 or 4 outputs. A typical application would be in building distribution of CDMA, GSM, DCS, PCS & WLAN signals. Features include: reliable, cost effective, light weight, durable construction, quick and easy installation.

Technical Specifications

Model:	TA-340 002 02	TA-340 002 03	TA-340 002 04
Product Type:	2-Way Splitter	3-Way Splitter	4-Way Splitter

Electrical Specifications

Frequency: (MHz)	698 – 3500		
Split Loss: (dB)	3	4.78	6
Insertion Loss: (dB)	< 0.3	< 0.5	< 0.7
Impedance : (Ohms)	50		
Maximum Input: (Watts)	100		
Connector:	N – Female		
VSWR:	1.3:1 Max		
Inter-modulation at 2*43 dBm Carrier: (dBc)	< - 140		

Mechanical Specifications


Dimensions: (L x W x H) (mm / in)	196.4 x 25 x 25 / 7.7 x 0.98 x 0.98		
Weight: (grams / lb)	350 / 0.77	370/0.81	390/0.85
Material:	Aluminum		
Finish:	Black Power Coat		

Environmental Specifications

Temperature Range: (Celsius)	- 20 to + 60		
------------------------------	--------------	--	--

Specifications subject to change without notice. Last updated: 2010.01.25.

Product Image



2-Way Splitter



3-Way Splitter



4-Way Splitter