

SINGLE BAND PANEL ANTENNA

BAND 850 MHz

AT41-665TX

824 - 896
H88° V10.1°
Fixed Tilt 0°, 2°, 4°, 6°


ELECTRICAL SPECIFICATIONS

BAND 850

Antenna Model	AT41-665TX
Polarization	Vertical
Frequency (MHz)	824 - 896
Horizontal Beamwidth	88°
Vertical Beamwidth	10.1°
Gain (dBi)	15
Vertical Electrical Tilt	FIXED 0°, 2°, 4°, 6°
Upper Sidelobe Suppression for the 1 st lobe above main beam (dB)	23
Front-to-Back Ratio @180° ± 20° (dB)	> 25
VSWR	< 1.4 : 1
Maximum Power Per Input (W)	500
Intermodulation (dBc)	< -150
Impedance (Ω)	50

MECHANICAL SPECIFICATIONS

Connectors	1 X 7/16 Female
Connector Position	Bottom
Survival Wind Speed km/h (mph)	200 (125)
Front Windload N @ 160 km/h (lbs @100 mph)	1045 (235)
Lateral Windload N @ 160 km/h (lbs @100 mph)	205 (46)
Radome Color	Grey, paintable
Humidity	100%
Antenna Weight kg (lbs)	18 (39)
Antenna Dimension mm (in) H X W X D	1985 X 325 X 115 (78 X 13 X 5)



H&V Pattern

