

# SINGLE BAND PANEL ANTENNA

## TA-2500-S400-17-60HV

2300-2700MHz
H60° V8°
Tilt 0°

### DESCRIPTION

- Directional antenna
- Dual linearly polarized
- Dual port

### ELECTRICAL SPECIFICATIONS

Antenna Model	TA-2500-S400-17-60HV
Polarization	Horizontal & Vertical
Frequency Band (MHz)	2300-2700
Gain (dBi)	17±1
Horizontal Beamwidth	60°±5°
Vertical Beamwidth	8°±2°
VSWR	1.3:1
Isolation (dB)	>27
Front-to-Back Ratio (dB)	>25
Cross Polar (dB) Typ.	>-15
Connector	2x 7/16" Female or 2x N Female
Power Handling (W)	160

### MECHANICAL SPECIFICATIONS

Dimensions H x W x D mm / (in)	1168 x 152.5 x 90 / (46 x 6 x 3.5)
Antenna Weight kg / (lbs)	6.35 / (14)
Connector Position	Bottom
Mounting Pipe O.D. mm / (in)	48 x 89 / (1.90 x 3.5)
Tilt Mechanism	Mechanical Tilt (Optional)
Radome	UV Stabilized ASA
Temperature Range	-40° to +60° C
Wind Speed km/h / (m/h)	160 / (100)



### ANTENNA PATTERN

